



PemGen

CHP-FCP-1000

The CHP-FCP-1000 is a Combined Heat Power PEM Fuel Cell Plant intended for co-generation applications in the built environment. The CHP-FCP-1000 is optimized for integration in fourth generation heat-grids and allows for seamless integration in electricity grids of all sorts by using commercial-off-the-shelf power electronics.





GENERAL	Fuel Cell Type	Low Temperature Proton Exchange Membrane (LT-PEM)
	Fuel Cell Model	120 x Nedstack FCS 13-XXL
CO-GENERATION OUTPUT	Max. Electric Power	1252 kWe
	Nominal Electric Power	1000 kWe
	Electrict Output Type	Configure to order
	Heat Output Power	1040 kW
	Heat Output Type	Heat exchanger interface @ 60-70°C
DIMENSIONS	Weight	29000 kg
	Built Level	40 ft ISO Container
	Length	12.19 m
	Width	2.44 m
	Height	2.59 m
HYDROGEN FEED	Quality	Grade ≥ 2.5 (CO < 0.2 ppm)
	Supply Pressure	0.3 - 6 barg
	Max. Consumption	90 kg/h
INTERNAL COOLANT	Coolant Type	DI water or BASF FC G20
ENVIRONMENTAL	Installation	Fit for outdoor installation
	Intended climate	Koppen class C: Mesothermal climates Other climatization packages available
APPLICATION	Intended Use	Residential blocks Commercial and insitutional facilities Chemical sites Ports
	Placement	To be placed on flat concrete surface
SAFETY	Compliancy	IEC-62282-2 IEC-62282-3 2006/95/EC 2006/42/EC 2004/108/EC