



Nedstack

PEM FUEL CELLS

PemGen[®] MT-FCPI-500



Nedstack fuel cell technology B.V.
Maritime Power Systems
www.Nedstack.com

Westervoortsedijk 73 VB
6827 AV ARNHEM
The Netherlands



PemGen[®]

MT-FCPI-500



The MT-FCPI-500 is a Maritime Fuel Cell Power Installation intended as a zero-emission shipping enabler. It offers a compact and robust LT-PEM power supply option for a large variety of maritime applications, both on inland waterways or in short-sea domain. The PemGen Fuel Cell Power System portfolio is available on a configure-to-order basis. Get in touch to tune this system to your application.



GENERAL	Fuel Cell Type	Low Temperature Proton Exchange Membrane (LT-PEM)
	Fuel Cell Model	60 x Nedstack FCS 13-XXL
ELECTRICAL	Nominal Power	500 kW _e
	Peak Power (BoL)	626 kW _e
	Voltage range	500 - 1000 VDC
	Current range	0 - 1200 A
ENCLOSURE	Weight	15.000 kg
	Built Level	20 ft ISO Container (High Cube)
	Length	6.06 m
	Width	2.44 m
	Height	2.90 m
	IP-rating	IP 54
	HYDROGEN FEED	Quality
Supply pressure		0.3 – 6 barg
Nominal consumption (BoL)		59 kg/ MWh _e
Max consumption		40 kg/h
COOLANT		Medium
	Outlet Temperature	Max 65 °C
	Required Cooling Capacity	900 kW _{th}
	Recoverable heat	>400 kW _{th}
AMBIENT CONDITIONS	Operating Temperature	-10 - 40 °C
	Storage Temperature	5 - 60 °C (optional -20 °C – 60 °C)
APPLICATION	Intended use	Main Propulsion Power for smaller vessel APU Source for Larger vessel
	Placement	Containerized when on open deck Skid based integration below deck
	Balance of Plant	20 years
	Stack Refurbishment	24k - 30k running hours
	COMPLIANCY	Standards